

The Revival of Active Set Methods

Sven Leyffer, leyffer@mcs.anl.gov

Mathematics & Computer Science Division, Argonne National Laboratory

1. Why Do We Need Active Set Methods?
2. Active Set Methods for Quadratic Programs
3. Active Set Methods for Nonlinear Programs

Why Do We Need Active Set Methods (ASMs)?



Philosophy Lesson

Issues in Optimization Solvers

$$\underset{x}{\text{minimize}} \ f(x) \quad \text{subject to} \ c(x) \geq 0$$

1. **Global Convergence**
2. **Active Set Identification**
3. **Fast Local Convergence**

Issues in Optimization Solvers

$$\underset{x}{\text{minimize}} \ f(x) \quad \text{subject to} \ c(x) \geq 0$$

1. Global Convergence

- merit function, e.g. $f(x) + \pi \|c(x)^-\|$ for $\pi > \|y^*\|_D$
- filter ... more later

2. Active Set Identification

3. Fast Local Convergence

Issues in Optimization Solvers

$$\underset{x}{\text{minimize}} \ f(x) \quad \text{subject to} \ c(x) \geq 0$$

1. Global Convergence

- merit function, e.g. $f(x) + \pi \|c(x)^-\|$ for $\pi > \|y^*\|_D$
- filter ... more later

2. Active Set Identification

- given active set, simply use Newton's method
- step computation: update estimate of active set
- alternative: interior point methods $Yc(x) = \mu e$ & $\mu \searrow 0$

3. Fast Local Convergence

Issues in Optimization Solvers

$$\underset{x}{\text{minimize}} \ f(x) \quad \text{subject to} \ c(x) \geq 0$$

1. Global Convergence

- merit function, e.g. $f(x) + \pi \|c(x)^-\|$ for $\pi > \|y^*\|_D$
- filter ... more later

2. Active Set Identification

- given active set, simply use Newton's method
- step computation: update estimate of active set
- alternative: interior point methods $Yc(x) = \mu e$ & $\mu \searrow 0$

3. Fast Local Convergence

- conjugate gradients et al.
- (constrained) preconditioners

Why Do We Need Active Set Methods (ASMs)?

Interior point methods (IPMs) usually faster than ASMs:

1. Pivoting **inefficient** for huge problems
2. Single QP solve \simeq **several Newton steps** of IPM
3. Null-space projected Hessian factors are **DENSE**

Why Do We Need Active Set Methods (ASMs)?

Interior point methods (IPMs) usually faster than ASMs:

1. Pivoting **inefficient** for huge problems
2. Single QP solve \simeq **several Newton steps** of IPM
3. Null-space projected Hessian factors are **DENSE**

Why should we be interested in ASMs?

- ASMs often more robust than interior point methods
- ASMs better for warm-starts (repeated solves)
- Easier to precondition ... iterative solves

Challenge: overcome 1. & 2. from above

Why Do We Need Active Set Methods (ASMs)?

Interior point methods (IPMs) usually faster than ASMs:

1. Pivoting **inefficient** for huge problems
2. Single QP solve \simeq **several Newton steps** of IPM
3. Null-space projected Hessian factors are **DENSE**

Why should we be interested in ASMs?

- ASMs often more robust than interior point methods
- ASMs better for warm-starts (repeated solves)
- Easier to precondition ... iterative solves

Challenge: overcome 1. & 2. from above

Two ways to make large changes to active set

1. Projected gradient approach
2. Sequential linear programming approach

ACTIVE SET METHODS FOR QPs

Active Sets for Quadratic Programs (QPs)

$$\begin{array}{ll}\underset{x}{\text{minimize}} & \frac{1}{2}x^T Hx + g^T x \\ \text{subject to} & A^T x = b \\ & l \leq x \leq u\end{array}$$

- H is symmetric (**indefinite?**)
- A^T is $m \times n$, $m < n$, full rank
- General: $\bar{l} \leq \begin{pmatrix} x \\ A^T x \end{pmatrix} \leq \bar{u}$

Active set $\mathcal{A}(x) = \{i \mid x_i = l_i \text{ or } x_i = u_i\}$

Inactive set $\mathcal{I}(x) = \{1, \dots, n\} - \mathcal{A}(x)$

Active Sets for Quadratic Programs (QPs)

Active set $\mathcal{A}(x) = \{i \mid x_i = l_i \text{ or } x_i = u_i\}$

Inactive set $\mathcal{I}(x) = \{1, \dots, n\} - \mathcal{A}(x)$

Given \mathcal{A} , QP solution $(x_{\mathcal{I}}^*, y^*)$ solves

$$\begin{bmatrix} H_{\mathcal{I},\mathcal{I}} & -A_{\cdot,\mathcal{I}} \\ A_{\cdot,\mathcal{I}}^T & \end{bmatrix} \begin{pmatrix} x_{\mathcal{I}} \\ y \end{pmatrix} = \begin{pmatrix} -g_{\mathcal{I}} - H_{\mathcal{I},\mathcal{A}}x_{\mathcal{A}} \\ b - A_{\cdot,\mathcal{A}}^Tx_{\mathcal{A}} \end{pmatrix}$$

Active-set methods search for \mathcal{A}^* :

- Delete entries from \mathcal{A}^k ; update a factorization; compute step
- Possibly add entries to \mathcal{A}^k
- \exists robust solvers; good for warm starts ... *n large ???*

PROJECTED GRADIENT


Projected Gradient for Box Constrained QPs

Simpler box constrained QP ...

$$\begin{cases} \underset{x}{\text{minimize}} & \frac{1}{2}x^T Hx + g^T x =: q(x) \\ \text{subject to} & l \leq x \leq u \end{cases}$$

Projected steepest descent $P[x - \alpha \nabla q(x)]$

- piecewise linear path
- ... large changes to \mathcal{A} -set
- ... but slow (steepest descent)



x^c Cauchy point \equiv first minimum of $q(x(\alpha))$, for $\alpha \geq 0$

Theorem: Cauchy points converge to stationary point.

Projected Gradient & CG for Box Constrained QPs

x^0 given such that $l \leq x^0 \leq u$; set $k = 0$

WHILE (not optimal) **BEGIN**

1. find Cauchy point x_k^c & active set $\mathcal{A}(x_k^c)$
2. (approx.) solve box QP in subspace $\mathcal{I} := \{1, \dots, n\} - \mathcal{A}(x_k^c)$

$$\underset{x}{\text{minimize}} \quad \frac{1}{2}x^T Hx + g^T x$$

$$\text{subject to} \quad l \leq x \leq u$$

$$x_i = [x_k^c]_i, \forall i \in \mathcal{A}(x_k^c)$$

\Leftrightarrow

apply CG to ...

$$H_{\mathcal{I}, \mathcal{I}} x_{\mathcal{I}} = \dots$$

for x^{k+1} ; set $k = k + 1$

END

Cauchy point \Rightarrow global convergence ... but faster due to CG

How to Include $A^T x = b$

Projection onto box is easy, but **tough** for general QP

$$P_{QP}[z] = \begin{cases} \underset{x}{\text{minimize}} & (x - z)^T(x - z) \\ \text{subject to} & A^T x = b \\ & l \leq x \leq u \end{cases}$$

... as hard as original QP! ... Idea: project onto box only

\Rightarrow subspace solve $H_{\mathcal{I},\mathcal{I}}x_{\mathcal{I}} = \dots$ becomes solve with KKT system

$$\begin{bmatrix} H_{\mathcal{I},\mathcal{I}} & -A_{\cdot,\mathcal{I}} \\ A_{\cdot,\mathcal{I}}^T & \end{bmatrix} \begin{pmatrix} x_{\mathcal{I}} \\ y \end{pmatrix} = \dots$$

Which **gradient** / **merit function** in Cauchy step?

AUGMENTED LAGRANGIAN

The Augmented Lagrangian

Arrow & Solow ('58), Hestenes ('69), Powell ('69)

$$\underset{x}{\text{minimize}} \quad L(x, y_k, \rho_k) = f(x) - y_k^T c(x) + \frac{1}{2} \rho_k \|c(x)\|^2$$

As $y_k \rightarrow y_*$: • $x_k \rightarrow x_*$ for $\rho_k > \bar{\rho}$

• No ill-conditioning, improves convergence rate

- An old idea for nonlinear constraints ... smooth merit function
- Poor experience with LPs (e.g., MINOS vs. LANCELOT)
- But special structure of LPs (and QPs) not fully exploited

$$f(x) = \frac{1}{2} x^T H x + g^T x \quad \& \quad c(x) = A^T x - b$$

Bound Constrained Lagrangian (BCL)

Minimizing the **augmented Lagrangian** subject to bounds:

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal x_k of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad f(x) - y_k^T c(x) + \frac{1}{2} \rho_k \|c(x)\|^2$$

Bound Constrained Lagrangian (BCL)

Minimizing the **augmented Lagrangian** subject to bounds:

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal x_k of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad f(x) - y_k^T c(x) + \frac{1}{2} \rho_k \|c(x)\|^2$$

2. **IF** $\|c(x_k)\| \leq \eta_k \searrow 0$ **THEN**

Update y_k (typically $y_{k+1} = y_k - \rho_k c(x_k)$)

ELSE increase ρ_k

END

Bound Constrained Lagrangian (BCL)

Minimizing the **augmented Lagrangian** subject to bounds:

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal x_k of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad f(x) - y_k^T c(x) + \frac{1}{2} \rho_k \|c(x)\|^2$$


2. **IF** $\|c(x_k)\| \leq \eta_k \searrow 0$ **THEN**
Update y_k (typically $y_{k+1} = y_k - \rho_k c(x_k)$)
ELSE increase ρ_k

END

Arbitrary sequences: η_k & ω_k control feasibility & optimality


Augmented Lagrangian for Linear Constraints

Nonlinear $c(x)$



$$(y_k, \rho_k) \in \mathcal{D}$$

$c(x) = A^T x - b$




$$\rho_k > \bar{\rho}$$

$\forall (\rho, y) \in \mathcal{D}$, minimize $L(x, y, \rho)$ has unique solution $x(y, \rho)$:

- bound constrained augmented Lagrangian converges
- Hessian $\nabla_{xx}^2 L(x, y, \rho)$ is positive definite on optimal face


Augmented Lagrangian for Linear Constraints

Nonlinear $c(x)$



$$(y_k, \rho_k) \in \mathcal{D}$$

$c(x) = A^T x - b$



$$\rho_k > \bar{\rho}$$

$\forall (\rho, y) \in \mathcal{D}$, minimize $L(x, y, \rho)$ has unique solution $x(y, \rho)$:

- bound constrained augmented Lagrangian converges
- Hessian $\nabla_{xx}^2 L(x, y, \rho)$ is positive definite on optimal face

$$\bar{\rho} \approx 2 \frac{\|H_*\|}{\|A_* A_*^T\|} \dots \text{depends on active set} \dots \text{from dual Hessian}$$

QP by Projected Augmented Lagrangian QPPAL

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal solution x_k^c of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad \frac{1}{2}x^T Hx + g^T x - y^T (A^T x - b) + \frac{1}{2}\rho_k \|A^T x - b\|^2$$

2. Find $\mathcal{A}(x_k^c)$ & estimate penalty $\bar{\rho} = 2 \|H_{\mathcal{I}}\| / \|A_{\mathcal{I}} A_{\mathcal{I}}^T\|$
3. **IF** $\bar{\rho} > \rho_k$ **THEN** update $\rho_{k+1} = \bar{\rho}$ & **CYCLE**
ELSE update multiplier: $y_k^c = y_k - \rho_k (A^T x_k^c - b)$

QP by Projected Augmented Lagrangian QPPAL

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal solution x_k^c of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad \frac{1}{2}x^T Hx + g^T x - y^T (A^T x - b) + \frac{1}{2}\rho_k \|A^T x - b\|^2$$

2. Find $\mathcal{A}(x_k^c)$ & estimate penalty $\bar{\rho} = 2 \|H_{\mathcal{I}}\| / \|A_{\mathcal{I}} A_{\mathcal{I}}^T\|$

3. **IF** $\bar{\rho} > \rho_k$ **THEN** update $\rho_{k+1} = \bar{\rho}$ & **CYCLE**

ELSE update multiplier: $y_k^c = y_k - \rho_k (A^T x_k^c - b)$

4. Solve equality QP in subspace $\rightarrow (\Delta_{x_{\mathcal{I}}}, \Delta y)$

$$\begin{bmatrix} H_{\mathcal{I}, \mathcal{I}} & -A_{:, \mathcal{I}} \\ A_{:, \mathcal{I}}^T & \end{bmatrix} \begin{pmatrix} \Delta x_{\mathcal{I}} \\ \Delta y \end{pmatrix} = - \begin{pmatrix} [\nabla_x L(x_k^c, y_k^c, 0)]_{\mathcal{I}} \\ A^T x_k^c - b \end{pmatrix}$$

QP by Projected Augmented Lagrangian QPPAL

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal solution x_k^c of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad \frac{1}{2}x^T Hx + g^T x - y^T (A^T x - b) + \frac{1}{2}\rho_k \|A^T x - b\|^2$$

2. Find $\mathcal{A}(x_k^c)$ & estimate penalty $\bar{\rho} = 2 \|H_{\mathcal{I}}\| / \|A_{\mathcal{I}} A_{\mathcal{I}}^T\|$

3. **IF** $\bar{\rho} > \rho_k$ **THEN** update $\rho_{k+1} = \bar{\rho}$ & **CYCLE**

ELSE update multiplier: $y_k^c = y_k - \rho_k (A^T x_k^c - b)$

4. Solve equality QP in subspace $\rightarrow (\Delta x_{\mathcal{I}}, \Delta y)$

$$\begin{bmatrix} H_{\mathcal{I}, \mathcal{I}} & -A_{:, \mathcal{I}} \\ A_{:, \mathcal{I}}^T & \end{bmatrix} \begin{pmatrix} \Delta x_{\mathcal{I}} \\ \Delta y \end{pmatrix} = - \begin{pmatrix} [\nabla_x L(x_k^c, y_k^c, 0)]_{\mathcal{I}} \\ A^T x_k^c - b \end{pmatrix}$$

5. Line-search on $L(x_k^c + \alpha \Delta x, y_k^c + \alpha \Delta y, \rho)$; **update** x, y, k, ρ

END

QP by Projected Augmented Lagrangian QPPAL

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal solution x_k^c of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad \frac{1}{2}x^T Hx + g^T x - y^T (A^T x - b) + \frac{1}{2}\rho_k \|A^T x - b\|^2$$

2. Find $\mathcal{A}(x_k^c)$ & estimate penalty $\bar{\rho} = 2 \|H_{\mathcal{I}}\| / \|A_{\mathcal{I}} A_{\mathcal{I}}^T\|$

3. **IF** $\bar{\rho} > \rho_k$ **THEN** update $\rho_{k+1} = \bar{\rho}$ & **CYCLE**

ELSE update multiplier: $y_k^c = y_k - \rho_k (A^T x_k^c - b)$

4. Solve equality QP in subspace $\rightarrow (\Delta x_{\mathcal{I}}, \Delta y)$

$$\begin{bmatrix} H_{\mathcal{I}, \mathcal{I}} & -A_{\cdot, \mathcal{I}} \\ A_{\cdot, \mathcal{I}}^T & \end{bmatrix} \begin{pmatrix} \Delta x_{\mathcal{I}} \\ \Delta y \end{pmatrix} = - \begin{pmatrix} [\nabla_x L(x_k^c, y_k^c, 0)]_{\mathcal{I}} \\ A^T x_k^c - b \end{pmatrix}$$

5. Line-search on $L(x_k^c + \alpha \Delta x, y_k^c + \alpha \Delta y, \rho)$; **update** x, y, k, ρ

END

- 1.-3. identify active set

QP by Projected Augmented Lagrangian QPPAL

WHILE (not optimal) **BEGIN**

1. Find $\omega_k \searrow 0$ optimal solution x_k^c of

$$\underset{l \leq x \leq u}{\text{minimize}} \quad \frac{1}{2}x^T Hx + g^T x - y^T (A^T x - b) + \frac{1}{2}\rho_k \|A^T x - b\|^2$$

2. Find $\mathcal{A}(x_k^c)$ & estimate penalty $\bar{\rho} = 2 \|H_{\mathcal{I}}\| / \|A_{\mathcal{I}} A_{\mathcal{I}}^T\|$

3. **IF** $\bar{\rho} > \rho_k$ **THEN** update $\rho_{k+1} = \bar{\rho}$ & **CYCLE**

ELSE update multiplier: $y_k^c = y_k - \rho_k (A^T x_k^c - b)$

4. Solve equality QP in subspace $\rightarrow (\Delta x_{\mathcal{I}}, \Delta y)$

$$\begin{bmatrix} H_{\mathcal{I}, \mathcal{I}} & -A_{\cdot, \mathcal{I}} \\ A_{\cdot, \mathcal{I}}^T & \end{bmatrix} \begin{pmatrix} \Delta x_{\mathcal{I}} \\ \Delta y \end{pmatrix} = - \begin{pmatrix} [\nabla_x L(x_k^c, y_k^c, 0)]_{\mathcal{I}} \\ A^T x_k^c - b \end{pmatrix}$$

5. Line-search on $L(x_k^c + \alpha \Delta x, y_k^c + \alpha \Delta y, \rho)$; **update** x, y, k, ρ

END

1.-3. identify active set ... 4. gives fast convergence

Filter Methods

A Filter for Augmented Lagrangian Methods

Two **competing aims** in augmented Lagrangian:

1. reduce $h_k := \|A^T x_k - b\| \leq \eta_k \searrow 0$
2. reduce $\theta_k := \|\nabla L(x_k, y_k, \rho_k) - z_k\| \leq \omega_k \searrow 0$

A Filter for Augmented Lagrangian Methods

Two **competing aims** in augmented Lagrangian:


1. reduce $h_k := \|A^T x_k - b\| \leq \eta_k \searrow 0$
2. reduce $\theta_k := \|\nabla L(x_k, y_k, \rho_k) - z_k\| \leq \omega_k \searrow 0$

... why should one sequence $\{\omega_k\}, \{\eta_k\}$ fit *all problems* ???

A Filter for Augmented Lagrangian Methods

Introduce a **filter** \mathcal{F} to promote convergence


- list of pairs $(\|A^T x_l - b\|, \|\nabla L_l - z_l\|)$
- no pair **dominates** any other pair
- new x_k **acceptable** to filter \mathcal{F} , iff
 1. $h_k \leq 0.99 \cdot h_l \forall l \in \mathcal{F}$
 2. $\theta_k \leq 0.99 \cdot \theta_l \forall l \in \mathcal{F}$



A Filter for Augmented Lagrangian Methods

Introduce a **filter** \mathcal{F} to promote convergence


- list of pairs $(\|A^T x_l - b\|, \|\nabla L_l - z_l\|)$
- no pair **dominates** any other pair
- new x_k **acceptable** to filter \mathcal{F} , iff
 1. $h_k \leq 0.99 \cdot h_l \forall l \in \mathcal{F}$
 2. $\theta_k \leq 0.99 \cdot \theta_l \forall l \in \mathcal{F}$
- **remove redundant entries**



A Filter for Augmented Lagrangian Methods

Introduce a **filter** \mathcal{F} to promote convergence


- list of pairs $(\|A^T x_l - b\|, \|\nabla L_l - z_l\|)$
- no pair **dominates** any other pair
- new x_k **acceptable** to filter \mathcal{F} , iff
 1. $h_k \leq 0.99 \cdot h_l \forall l \in \mathcal{F}$
 2. $\theta_k \leq 0.99 \cdot \theta_l \forall l \in \mathcal{F}$
- **remove redundant entries**
- **reject new x_k , if $h_k \geq h_l$ & $\theta_k \geq \theta_l$**



A Filter for Augmented Lagrangian Methods

Introduce a **filter** \mathcal{F} to promote convergence

- list of pairs $(\|A^T x_l - b\|, \|\nabla L_l - z_l\|)$
- no pair **dominates** any other pair
- new x_k **acceptable** to filter \mathcal{F} , iff
 1. $h_k \leq 0.99 \cdot h_l \forall l \in \mathcal{F}$
 2. $\theta_k \leq 0.99 \cdot \theta_l \forall l \in \mathcal{F}$
- **remove redundant entries**
- **reject new x_k , if $h_k \geq h_l$ & $\theta_k \geq \theta_l$**



... and old friend from Chicago ...

Augmented Lagrangian Cauchy Point (Al Capone)

Requirement on Cauchy Point x_k^c for filter:


1. x_k^c, y_k^c acceptable to filter



Augmented Lagrangian Cauchy Point (Al Capone)

Requirement on Cauchy Point x_k^c for filter:

1. x_k^c, y_k^c acceptable to filter
2. $\|\nabla L(x_k, y_k, \rho_k) - z_k\| \leq \omega_k$
... optimality of Lagrangian




Augmented Lagrangian Cauchy Point (Al Capone)

Requirement on Cauchy Point x_k^c for filter:

1. x_k^c, y_k^c acceptable to filter
2. $\|\nabla L(x_k, y_k, \rho_k) - z_k\| \leq \omega_k$
... optimality of Lagrangian

New: $\omega_k := 0.1 \max \{\|\nabla L_l - z_l\|\}$
... depends on filter




Augmented Lagrangian Cauchy Point (Al Capone)

Requirement on Cauchy Point x_k^c for filter:

1. x_k^c, y_k^c acceptable to filter
2. $\|\nabla L(x_k, y_k, \rho_k) - z_k\| \leq \omega_k$
... optimality of Lagrangian

New: $\omega_k := 0.1 \max \{\|\nabla L_l - z_l\|\}$
... depends on filter

1. ensures that back-tracking line-search will succeed
... if **not acceptable** then reduce $\omega_{k+1} = \omega_k/2$




Augmented Lagrangian Cauchy Point (Al Capone)

Requirement on Cauchy Point x_k^c for filter:

1. x_k^c, y_k^c acceptable to filter
2. $\|\nabla L(x_k, y_k, \rho_k) - z_k\| \leq \omega_k$
... optimality of Lagrangian

New: $\omega_k := 0.1 \max \{\|\nabla L_l - z_l\|\}$
... depends on filter




1. ensures that back-tracking line-search will succeed
... if **not acceptable** then reduce $\omega_{k+1} = \omega_k/2$
2. & $\omega_{k+1} = \omega_k/2$ ensure new entry can be added to filter

Augmented Lagrangian Cauchy Point (Al Capone)

Requirement on Cauchy Point x_k^c for filter:

1. x_k^c, y_k^c acceptable to filter
2. $\|\nabla L(x_k, y_k, \rho_k) - z_k\| \leq \omega_k$
... optimality of Lagrangian

New: $\omega_k := 0.1 \max \{\|\nabla L_l - z_l\|\}$
... depends on filter



1. ensures that back-tracking line-search will succeed
... if **not acceptable** then reduce $\omega_{k+1} = \omega_k/2$
2. & $\omega_{k+1} = \omega_k/2$ ensure new entry can be added to filter

Why do you keep the penalty parameter?


... combines search directions for $\|A^T x - b\|$, and

$\|\nabla L(x_l, y_l, \rho_l) - z_l\|$

\Rightarrow gradient projection possible

Active Set Evolution: blockqp4_100

AUGLAG




red = lower bound active


green = upper bound active

Active Set Evolution: blockqp4_100

AUGLAG



FILTER



red = lower bound active
green = upper bound active

Summary: Active Set QP Method

1. **Global Convergence**
2. **Active Set Identification**
3. **Fast Local Convergence**

Summary: Active Set QP Method

1. Global Convergence

- augmented Lagrangian & filter
⇒ no arbitrary parameters

2. Active Set Identification

3. Fast Local Convergence

Summary: Active Set QP Method

1. Global Convergence

- augmented Lagrangian & filter
⇒ no arbitrary parameters

2. Active Set Identification

- projected gradient on augmented Lagrangian
- easy penalty parameter estimate

3. Fast Local Convergence

Summary: Active Set QP Method

1. Global Convergence

- augmented Lagrangian & filter
⇒ no arbitrary parameters

2. Active Set Identification

- projected gradient on augmented Lagrangian
- easy penalty parameter estimate

3. Fast Local Convergence

- conjugate gradients on equality QP
- (constrained) preconditioners ???
- Benzi-Golub ... ties in with augmented Lagrangian

ACTIVE SET METHODS FOR NLPs

Sequential Quadratic Programming (SQP)

$$\text{NLP:} \quad \underset{x}{\text{minimize}} \quad f(x) \quad \text{subject to} \quad c(x) \geq 0$$

SQP method of choice for NLP

Compute displacement/step d by solving QP subproblem

$$\begin{array}{ll} \underset{d}{\text{minimize}} & g^T d + \frac{1}{2} d^T W d \\ \text{subject to} & c + A^T d \geq 0 \\ & \|d\|_{\infty} \leq \Delta \end{array} \quad \text{Trust-Region}$$

where $g = \nabla f(x)$, $A = \nabla c(x)^T$, $W = \nabla^2 \mathcal{L}(x, y)$

Sequential Quadratic Programming (SQP)

WHILE (not optimal) **BEGIN**

1. Compute displacement/step d by solving QP subproblem
2. **IF** step d acceptable **THEN**

$x = x + d$ & increase trust-region radius $\Delta = 2 * \Delta$

ELSE

$x = x$ & decrease trust-region radius $\Delta = \Delta/2$

END

- How to make it work for n large ???
QP solve is bottleneck ... could use new QPFIL
- \exists excellent LP solvers ... but QP harder

Sequential Linear Programming

Throw away quadratic term \Rightarrow linear program

Compute displacement/step d_{LP} by solving LP subproblem

$$\begin{array}{ll} \underset{d}{\text{minimize}} & g^T d + \frac{1}{2} d^T W d \\ \text{subject to} & c + A^T d \geq 0 \\ & \|d\|_{\infty} \leq \Delta \end{array} \quad \text{Trust-Region}$$

where $g = \nabla f(x)$, $A = \nabla c(x)^T$, $W = \nabla^2 \mathcal{L}(x, y)$

Sequential Linear Programming

WHILE (not optimal) **BEGIN**

1. Compute displacement/step d_{LP} by solving LP subproblem

3. **IF** step d acceptable **THEN**

$x = x + d$ & increase trust-region radius $\Delta = 2 * \Delta$

ELSE

$x = x$ & decrease trust-region radius $\Delta = \Delta/2$

END

\Rightarrow slow local convergence ... steepest descent

Sequential Linear Programming

WHILE (not optimal) **BEGIN**

1. Compute displacement/step d_{LP} by solving LP subproblem
2. Identify active constraints: $\mathcal{A} = \{i : c_i + a_i^T d_{LP} = 0\}$ & solve

$$\begin{array}{ll} \underset{d}{\text{minimize}} & g^T d + \frac{1}{2} d^T W d \\ \text{subject to} & c_i + a_i^T d = 0 \quad i \in \mathcal{A} \end{array} \Leftrightarrow \begin{bmatrix} H_{\mathcal{I}, \mathcal{I}} & -A_{:, \mathcal{I}}^T \\ A_{:, \mathcal{I}} & \end{bmatrix} \begin{pmatrix} d_{\mathcal{I}} \\ y \end{pmatrix}$$

equality QP for step d

3. **IF** step d acceptable **THEN**

$x = x + d$ & increase trust-region radius $\Delta = 2 * \Delta$

ELSE

$x = x$ & decrease trust-region radius $\Delta = \Delta/2$

END

How expensive are LPs??

Active Set Identification by SLP

Polyhedral trust-region makes LP solves inefficient

$$\begin{array}{ll} \underset{d}{\text{minimize}} & g^T d \\ \text{subject to} & c + A^T d \geq 0 \\ & \|d\|_\infty \leq \Delta \quad \text{Trust-Region} \end{array}$$

- many changes to active trust-region bounds
- LP solvers too slow near solution

Active Set Identification by SLP

Ellipsoidal trust-region makes LPs into NLPs

$$\begin{array}{ll} \underset{d}{\text{minimize}} & g^T d \\ \text{subject to} & c + A^T d \geq 0 \\ & \|d\|_2 \leq \Delta \end{array} \quad \text{Trust-Region}$$

- trust-region (always) active \Rightarrow no changes
- subproblem is now NLP ... as hard as original problem ???

Active Set Identification by SLP

Ellipsoidal trust-region makes LPs into NLPs

$$\begin{array}{ll} \underset{d}{\text{minimize}} & g^T d \\ \text{subject to} & c + A^T d \geq 0 \\ & d^T d \leq \Delta^2 \end{array} \quad \text{Trust-Region}$$

- trust-region (always) active \Rightarrow no changes
- subproblem is now NLP ... as hard as original problem ???

Summary: Active Set NLP Method

1. **Global Convergence**
2. **Active Set Identification**
3. **Fast Local Convergence**

Summary: Active Set NLP Method

1. Global Convergence

- Sequential bound constraint
- Trust-region & Filter

2. Active Set Identification

3. Fast Local Convergence

Summary: Active Set NLP Method

1. Global Convergence

- Sequential bound constraint
- Trust-region & Filter

2. Active Set Identification

- d_{LP} LP steps from subproblem

3. Fast Local Convergence

Summary: Active Set NLP Method

1. Global Convergence

- Sequential bound constraint
- Trust-region & Filter

2. Active Set Identification

- d_{LP} LP steps from subproblem

3. Fast Local Convergence

- conjugate gradients on equality QP
- (constrained) preconditioners ???